SOLID HIGH MOLECULAR ELECTROLYTE TYPE FUEL CELL

Patent number: JP5094832
Publication date: 1993-04-16

Inventor: NISHIHARA YOSHINORI
Applicant: FUJI ELECTRIC CO LTD

Classification:

- International: H01M8/04; H01M8/10

- european: H01M8/04C2E

Application number: JP19910252637 19911001


Priority number(s): JP19910252637 19911001

Report a data error here

Abstract of JP5094832

PURPOSE:To increase the reaction gas amount passing through a cell as well as to make it possible to operate the cell stably, by providing humidifiers in the loops of a fuel cell, and adding the steam to the reaction gas so as to maintain a solid high polymer electrolyte in a wetting condition constantly.

CONSTITUTION:Recycle loops 7 and 8 are provided newly, and pumps 6 and 4 are provided in the loops 7 and 8. And a reaction gas recycled by the loops is led to a cell through humifiers 5, and in this case, the number of passing is made numerous, and the including amount of steam is increased to make it possible to feed a necessary amount of moisture. And the reflux ratio of the recycled reaction gas is set as desired in the relation with the output property of the cell. Although a bubbler is used as the humidifier, a steam generator, an ultrasonic humidifier, an internal humidifier, and the like can be used instead of the bubbler.



Data supplied from the **esp@cenet** database - Worldwide